



SICHERUNGSBÜGEL LOCKING CLIPS



Abmessung Dimension					Sechskant- schraube Hex head screw	Anzieh- drehmoment Tightening turning moment	Gewicht Weight	Kurzzeichen Designation
s	bs	h	ds	e				
mm						Nm	kg	
4	20	12	7	13,5	M6x10	19	0,026	MS3044
4	20	12	9	17,5	M8x16	42	0,035	MS3048
4	24	12	9	17,5	M8x16	42	0,042	MS3056
4	24	12	9	20,5	M8x16	42	0,045	MS3060
4	24	12	12	30,5	M10x18	85	0,064	MS3160
5	24	15	9	21	M8x16	42	0,058	MS3064
5	24	15	12	31	M10x18	85	0,079	MS3164
5	28	15	14	38	M12x22	130	0,107	MS3168
5	28	15	9	20	M8x16	42	0,063	MS3072
5	28	15	12	24	M10x18	85	0,079	MS3076
5	32	15	14	40	M12x22	130	0,121	MS3176
5	32	15	18	45	M16x25	330	0,164	MS3180
5	32	15	12	24	M10x18	85	0,087	MS3084

SICHERUNGSBÜGEL LOCKING CLIPS



Abmessung Dimension					Sechskant- schraube Hex head screw	Anzieh- drehmoment Tightening turning moment	Gewicht Weight	Kurzzeichen Designation
s	bs	h	ds	e				
mm						Nm	kg	
5	32	15	14	28	M12x22	130	0,105	MS3088
5	36	15	18	43	M16x25	330	0,172	MS3188
5	36	15	14	28	M12x22	130	0,114	MS3096
5	36	15	18	53	M16x25	330	0,186	MS3196
5	40	15	18	45	M16x25	330	0,187	MS31/500
7	40	21	18	34	M16x25	330	0,229	MS30/530
7	40	21	18	29	M16x25	330	0,218	MS30/560
7	45	21	18	34	M16x25	330	0,248	MS30/630
7	45	21	18	39	M16x25	330	0,261	MS30/670
7	50	21	18	39	M16x25	330	0,283	MS30/710
7	55	21	18	39	M16x25	330	0,304	MS30/750
7	60	21	22	44	M20x40	430	0,424	MS30/850
7	60	21	22	46	M20x40	430	0,43	MS30/950